

PATH TO THE FUTURE

Inspired by the rigorous quality testing in the production of MSI G series, MSI G series' design is full of symbols of sturdiness and durability. Additionally, to provide quality user experience, G series has really simple installation process and a friendly user interface, and will be the best choice for entry level gamers to step into the game world.



Picture and logos

SELLING POINTS

- Curved Gaming display (1500R) - The best gameplay immersion.
- 250Hz Refresh Rate - Real smooth gaming.
- 1ms response time - eliminate screen tearing and choppy frame rates.
- Wide Color Gamut - Game colors and details will look more realistic and refined, to push game immersion to its limits.
- Adaptive sync Technology - Tear free, stutter free, fluid gaming.
- Anti-Flicker and Less Blue Light - game even longer and prevent eye strain and fatigue.
- Frameless design - Ultimate gameplay experience.
- 178° wide view angle.



1. 5-way joystick navigator
2. 1 x DC Jack
3. 1 x Display Port 1.2a
4. 2 x HDMI™ 2.0
5. 1 x Earphone out
6. 1 x Kensington lock

SPECIFICATION

Model	Entity MKT Name	G32C4X
	Part No	9S6-3DA61T-051
	Color	ID1/Black-Black
Display	Screen Size	31.5" (80 cm)
	Active Display Area (mm)	698.4(H)x392.85(V)
	Curvature	Curve 1500R
	Panel Type	VA
	Resolution	1920x1080 (FHD)
	Pixel pitch (mm)	0.36375(H)x0.36375(V)
	Aspect Ratio	16:9
	Dynamic Refresh Rate technology	FreeSync Premium
	Dynamic Refresh Rate Activated Range	96 ~ 250Hz
	HDR (High dynamic range)	HDR Ready
	SDR Brightness (nits)	300
	Contrast Ratio	3000:1
	DCR (Dynamic Contrast Ratio)	10000000:1
	Signal Frequency	242~277 KHz(H) / 96~250 Hz(V)
	Refresh Rate	250Hz
	Response Time (MPRT)	1ms(MPRT)
	Response Time (GTG)	4ms
	View Angles	178°(H)/178°(V)
	NTSC (CIE1976 area percentage/overlap)	100.07%/86.78%
	NTSC (CIE1931 area percentage/overlap)	85.94%/80.71%
	sRGB (CIE1976 area percentage/overlap)	114.77%/97.72%
	sRGB (CIE1931 area percentage/overlap)	121.34%/99.39%
	Adobe RGB (CIE1976 area percentage/overlap)	98.35%/89.62%
	Adobe RGB (CIE1931 area percentage/overlap)	89.93%/83.53%
	DCI-P3 (CIE1976 area percentage/overlap)	91.4%/91.08%
	DCI-P3 (CIE1931 area percentage/overlap)	89.45%/89.28%
	Rec.709 (CIE1976 area percentage/overlap)	114.77%/97.72%
	Rec.709 (CIE1931 area percentage/overlap)	121.34%/99.39%
	Rec.2020 (CIE1976 area percentage/overlap)	66.6%/66.6%
	Rec.2020 (CIE1931 area percentage/overlap)	64.17%/64.17%
	Surface Treatment	Anti-glare
	Display Colors	1.07B
	Color bit	10 bits (8 bits + FRC)
I/O Ports	Headphone-out	1
	Lock type	Kensington Lock
	HDMI	2
	HDMI version	2.0b
	HDMI HDCP version	2.3
	DisplayPort	1
	DisplayPort version	1.2a
	DisplayPort HDCP version	2.3
Warranty	Warranty	36M
Power	Power Type	External Adaptor 20V 3.25A
	Power Input	100~240V, 50/60Hz
	On-mode Power Consumption (KWh/1000h)	26
	Standby-mode Power Consumption (W)	0.5
	Off-mode Power Consumption (W)	0.3
	Energy Efficiency Rating	F
Power Cord Type	C5	

In The Box	DisplayPort Cable	1
	HDMI Cable	0
	DVI Cable	0
	USB Type A to Type B Cable	0
	USB Type C to Type A Cable	0
	USB Type C to Type C Cable	0
	Thunderbolt Cable	0
	VGA Cable	0
	3.5mm audio Cable	0
	3.5mm combo audio Cable	0
	3.5mm Mic Cable	0
	Power Cord	1
	AC Adaptor	1
	Quick Guide	1
	Warranty Card	0
Mouse Bungee Unit	0	
Design	Adjustment (Tilt)	-5° ~ 20°
	VESA Mounting	100x100mm
Dimension & Weight (product)	Product Dimension with Stand (WxDxH) (mm)	709.4 x 248.7 x 509.4
	Product Dimension without Stand (WxDxH) (mm)	709.4 x 92 x 429.3
	Stand Dimension (WxDxH) (mm)	452.8 x 248.7 x 265.5
	Weight (Net kg)	6.3
	Weight Without Stand (kg)	5.5
Dimension & Weight (box)	Inside Carton Dimension (WxDxH) (cm)	16.8 x 97 x 51.3
	Outer Carton Dimension (WxDxH) (cm)	18.3 x 98.5 x 53.8
	Weight (Gross kg)	9.
Barcode Info	EAN	4711377254670